

261kWh Cabinet C&I ESS Liquid-Cooling

- *Demand Regulation*
- *Peak Shaving*
- *Comprehensive Energy Utilization*



Model	ESS-C-JG261A-L
AC Input/Output	
AC Rated Power	125kW
AC Rated Voltage	230V/400V, 3P+N+PE
Rated Frequency	50Hz/60Hz
Power Factor	0.8(Leading)~0.8(Lagging)
THDi	3%
Off-grid	Support
Battery Parameters	
Rated Capacity	261Wh
Max.DC Current	172A
Battery Type	LFP 3.2V / 314Ah
DC Rated Voltage	832V
DC Battery Voltage Range	728~936V
Battery Module	166.4V / 52.249kWh
Battery System Configuration	1P260S
General	
Size(W*D*H)	1050mm×1350mm×2350mm
Total Weight	~2.7t
Cooling Method	Liquid Cooling
Operating Temperature	-20℃~+45℃
Humidity	5-95%RH(Non-Condensing)
Altitude	≤2000m
Noise Emission	≤75dB
IP Rating	IP54
Fire Extinguishing System	Aerosol
Compliance	IE/CEN62477-1, IEC/EN 61000-6-2, IEC/EN 61000-6-4, IEC62619, G99, G100, AS47772, EN 50549-1, VDE-AR-N 4105, UN38.3



Shenzhen Ancheng New Energy Co.,Ltd

☎ 0755-89210030 ✉ ac@anchengne.com 🌐 <http://www.anchengne.com>

📍 401, Airfact Office Building, Qigui Road 2, Nanbu Community, Longtian Street, Pingshan District, Shenzhen, Guangdong, China